

[INSTRUCTION: Amend as required; delete all Blue Text prior to release]

# DASH Projects BIM Requirements

[Project Name]

1. REFERENCE TABLES AND LISTS

1.1 TABLE OF REVISIONS

Description	Date	Author	Version
First publication	June 2024	V. Carignan	1
October Revision	October 2024	J.-M. Couffin	2
October Revision	October 2025	V. Carignan	3

1.2 LIST OF TABLES

Table 1 - References for BIM Requirements .....5

Table 2 - Lead BIM Manager Responsibilities.....7

Table 3 - Responsibilities of the BIM Discipline Manager .....8

Table 4 - BIM uses.....9

Table 5 - BIM Design Kick-off Meeting .....15

Table 6 - BIM management meeting .....15

Table 7 - Design Coordination Meetings .....15

**1.3 TABLE OF CONTENTS**

<b>1. Reference tables and lists .....</b>	<b>2</b>
1.1 Table of Revisions .....	2
1.2 List of Tables.....	2
1.3 Table of Contents .....	3
<b>2. Reference documents and standards.....</b>	<b>5</b>
2.1 Project-specific References .....	5
2.1.1 BIM Requirements and other BIM References .....	5
<b>3. Objectives of this Document.....</b>	<b>5</b>
<b>4. Project Overview .....</b>	<b>6</b>
4.1 Context.....	6
4.2 BIM Objectives for the Project.....	6
<b>5. Team Organization .....</b>	<b>7</b>
5.1 Roles and responsibilities.....	7
5.1.1 Scope of Responsibility .....	7
5.1.2 Lead BIM Manager – Prime Consultant .....	7
5.1.3 BIM Managers (Consultants).....	8
<b>6. BIM Uses .....</b>	<b>9</b>
6.1 Modeling .....	9
6.1.1 Modeling Requirements by Discipline .....	9
6.1.2 Model Breakdown.....	10
6.1.3 Master File .....	10
6.1.4 Georeferencing .....	10
6.1.5 Elements Breakdown .....	10
6.2 Design Coordination.....	11
6.3 Production of 2D Deliverables Extracted from Models .....	11
<b>7. BIM Deliverables .....</b>	<b>12</b>
<b>8. BIM Management Process.....</b>	<b>13</b>
8.1 Collaboration Process .....	13
8.1.1 Common Data Environment (CDE).....	13
8.1.2 BIM Meetings.....	14

8.2	Design Change management .....	15
9.	Quality Assurance and Control .....	16
9.1	Quality Assurance Plan.....	16

## 2. REFERENCE DOCUMENTS AND STANDARDS

### 2.1 PROJECT-SPECIFIC REFERENCES

#### 2.1.1 BIM REQUIREMENTS AND OTHER BIM REFERENCES

The purpose of the BIM Requirements document is to provide clear and precise requirements for [Developer Name] BIM projects.

Table 1 - References for BIM Requirements

PRECEDENCE	DOCUMENT	DESCRIPTION
1	Contract and technical specifications from Design phase, preliminary plans and specifications	General clauses, properties, risk and reliability, list of deliverables for the Design phase, preliminary plans and specifications
1	Contracts, plans and technical specifications for construction work	General clauses, properties, risk and reliability, list of deliverables for construction work
2	BIM Requirements	Organization and general requirements of a BIM project
2	BIM Requirements - Appendix : Information requirements	Specific requirements for project information creation and management
3	BIM Execution Plan (BEP)	Methods and resources put in place to meet the requirements of [Developer Name]. Produced by the Prime Consultant.

## 3. OBJECTIVES OF THIS DOCUMENT

This document constitutes the BIM Requirements for the [Project Name] project and is an integral part of the project's requirements. It defines:

- The contractual BIM Requirements of [Developer Name] for this project.
- The BIM uses to be implemented on the project.
- The scope and information requirements to include in the Models required for the project.
- BIM-related roles and responsibilities for stakeholders involved in the project.

## 4. PROJECT OVERVIEW

### 4.1 CONTEXT

[\[Add Project Description and Details\]](#)

### 4.2 BIM OBJECTIVES FOR THE PROJECT

- Achieve a high-level of design resolution and coordination to minimize uncertainty in construction. This objective requires well-coordinated three-dimensional models and corresponding two-dimensional Construction Documents.
- Achieve an efficient and straightforward BIM workflow that doesn't require intensive management on the part of [\[Developer Name\]](#) or the Design Team.
- Support the Optimized Design Process in the context of the DASH demo projects

## 5. TEAM ORGANIZATION

### 5.1 ROLES AND RESPONSIBILITIES

#### 5.1.1 SCOPE OF RESPONSIBILITY

The Prime Consultants shall identify a Lead BIM Manager who will be the interface of [Developer Name] for all matters relating to BIM. General responsibilities are described in the technical specifications. All activities related to the responsibilities described below must be carried out in compliance with the BIM and information requirements.

#### 5.1.2 LEAD BIM MANAGER – PRIME CONSULTANT

Table 2 - Lead BIM Manager Responsibilities

CATEGORY	RESPONSIBILITIES
Management	Coach BIM Managers in BIM planning and implementation for the current phase
	Assist BIM Managers in defining their model quality assurance plan throughout the current phase.
	Assist BIM Managers in defining their procedure for checking conformity between the reality built on site and the construction models as work progresses.
	Structure, coordinate and enforce BIM processes and usages required for the design phase.
Scheduling	Coordinate the delivery of BIM models and deliverables for each sub-consultant
	Establish, in collaboration with project managers and BIM managers, the schedule for modeling, coordination and design reviews
BIM Execution Plan	Create and manage the design BIM Execution Plan (BEP) in collaboration with the BIM Managers of each sub-consultant
BIM meetings	Pilot the visualization of the Models at each meeting with [Developer Name]
	Organize and lead BIM management meetings useful for coordinating the process within the design team and take minutes to ensure follow-up
Modeling	Create and update the Master File for the project
	Implement georeferencing on the project, determining the best approach according to the type of project ensuring that all disciplines always share the same coordinates
	Coordinate the placement of premises (including rooms and spaces) between discipline BIM Managers
	Define an intervention sequence with the discipline BIM Managers for space coding for MEP sub-consultants
Coordination	Produce coordination reports at the close of an interdisciplinary 3D coordination cycle by: <ul style="list-style-type: none"> <li>Visual inspections.</li> <li>Automated clash detection.</li> </ul>

Quality	Create and manage the quality assurance plan and integrate it into the BIM Execution Plan (BEP)
	Ensure that BIM and information requirements are met by sub-consultants
	Ensure that [Developer Name] standards are followed on the project
	Carry out the required quality controls before handing over BIM deliverables
Common Data Environment (CDE)	Set up a collaborative platform for the project, to be approved by [Developer Name]
	For each tool implemented on the project, ensure the maintenance of a documentation structure in line with the standards of the project and communicate this through the BIM Execution Plan (BEP).
	Ensure the relevant participation and use of the CDE by the sub-consultants. This includes: <ul style="list-style-type: none"> <li>Organize training sessions as needed, depending on the tools in place</li> <li>Continuous monitoring and updating of platform information</li> <li>Monitoring and updating the list of users of these platforms</li> </ul>

### 5.1.3 BIM MANAGERS (CONSULTANTS)

Table 3 - Responsibilities of the BIM Discipline Manager

CATEGORY	RESPONSIBILITIES
Management	Manages the BIM team of a particular sub-consultant for the project
BIM Execution Plan	Write and maintain the part of the BIM Execution Plan (BEP) related to the relevant discipline
Collaboration	Ensures models sharing at the defined frequency
	Act as the interface for the relevant discipline with BIM Managers and modelers from other disciplines
Modeling	Control the creation of new models for the discipline
	Identifies the need for shared interdisciplinary parameters
	Manages the creation of BIM content related to its responsibilities
	Ensures that all of [Developer Name] requirements defined in the Appendix - Information requirements are met
Documentation / 2D drawings	Extract all relevant 2D deliverables from design Models
Coordination	Ensures 3D intradisciplinary coordination for your discipline before sharing information with other disciplines and specialties.
	Establish, in conjunction with the Lead BIM Manager, the schedule for coordination reviews
Quality	Ensures intradisciplinary quality control before submission to the project team
	Ensures that the team's models comply with modeling requirements, and that the required information is modeled at the right time.
	Validate with a conformity check that their concept is respected in the construction Models. The required conformity check includes a visual inspection of the superimposition of the Design Models and the Construction Models.
Common Data Environment (CDE)	Ensure that models are classified as required on the CDE
	Ensure the active participation of your team on the CDE used on the project



## 6. BIM USES

Table 4 - BIM uses

USES	SPECIFIC REQUIREMENTS	RESPONSIBLE
<b>Design Modeling</b>	A process in which 3D modeling software are used to develop information-rich models based on design criteria.	All
<b>Design Optimization</b>	Leverage models to iteratively refine and optimize design solutions aligned with DASH initiative objectives (prefabricability, repeatability, standardization, etc.)	All
<b>Design Coordination</b>	Visual inspections and automated interference detection are necessary to meet quality requirements on the project. Any coordination issues raised must be analyzed, sorted and tracked throughout the project, while documenting the steps taken to resolve them.	All
<b>Production of 2D deliverables extracted from Models</b>	Documentation must be extracted from the models after interdisciplinary coordination (no alterations via another CAD software) and must complement and enhance the modeling, without contradicting or diverging from it.	All
<b>Construction Model Review</b>	Review construction models from trade contractors to verify design intent compliance.	All
<b>Model Visualization for Design and Construction Support</b>	Display and navigate current models during meetings to enable effective project communication and decision-making.	All

### 6.1 MODELING

#### 6.1.1 MODELING REQUIREMENTS BY DISCIPLINE

The following disciplines are expected to model according to the requirements laid out in BIM Requirements Appendix – Information Requirements.

- Architecture
- Structure
- Mechanical
- Electrical
- Communications
- Security

The following disciplines are not expected to model during Design:

- Fire Protection
- Civil
- Landscape
- Audio-Visual
- Lighting

- Vertical Transportation
- Surveyor

---

#### 6.1.2 MODEL BREAKDOWN

The division of the project into individual models proposed by the parties involved must be specified in the BIM Execution Plan (BEP) and approved by [Developer Name]. BIM Managers are responsible for ensuring that the breakdown complies with the requirements and standards of [Developer Name] requirements and standards defined in the BIM Requirements (e.g. maximum file size, location limits, etc.).

---

#### 6.1.3 MASTER FILE

This Model is created by the Lead BIM Manager and is specific to the project. It serves as the main source for all the elements useful for positioning and identifying the limits of the project, namely:

- Shared coordinate system (site) and georeferencing
- Reference axes (grids) for the location
- The "NS" (North-South) and "EO" (East-West) orientation axes intersecting the geodetic marker selected as reference for the project
- Levels for the location concerned (all disciplines and/or specialties combined)
- Property limits for the location

---

#### 6.1.4 GEOREFERENCING

All models must be georeferenced in accordance with the following principles:

- The Canadian NAD83 system must be used
- The Master File should be used as a reference source

Stakeholders involved in the implementation of georeferencing must ensure that the following conditions are met at all times on the project:

- Apart from the inherent project issues, the method used must allow for a global relocation of the project or a change of coordinate system.
- The method used must enable all stakeholders to produce models that are correctly geolocated and aligned with each other, particularly when they are federated or viewed on the platforms set up for the project.

---

#### 6.1.5 ELEMENTS BREAKDOWN

- Elements must be specifically modeled in such a way that they are easily transmitted to other platforms through open BIM formats:
- Walls and structural elements must be split by level
- Walls must be identified by their functional use: Interior, Exterior, Core Circulation, Foundation, Etc.

## **6.2 DESIGN COORDINATION**

Each BIM Manager is responsible for ensuring the coordination of their Design Models.

In addition to continuous visual detection of coordination problems based on Models, automated clash detection between various design will be planned and carried out as the project progresses. To ensure the relevance and effectiveness of these checks, the Models used must first have been validated by each BIM Manager. Here is a summary list of the verifications required:

- The file format complies with project standards
- The level of information need and geometry complies with the BIM Requirements
- Models are up to date and contain local modifications made by all users
- The model is correctly georeferenced

## **6.3 PRODUCTION OF 2D DELIVERABLES EXTRACTED FROM MODELS**

Tender and construction drawings must be extracted from the coordinated design models. The specific annotations indicated on these plans must be generated directly from the alphanumeric information attached to the model elements.

## 7. BIM DELIVERABLES

BIM DELIVERABLES	RESPONSIBLE	FORMAT	NOTES
<b>BIM Execution Plan</b>	Lead BIM Manager	.pdf	The BIM Execution Plan is part of the Project Protocols to be developed by the Prime Consultant (see 2.1 in Appendix 7). Each Consultant will contribute to the BEP by providing their model structure.
<b>Meeting Minutes</b>	Lead BIM Manager	.pdf	For : <ul style="list-style-type: none"> <li>• BIM Kickoff Meeting Minutes</li> <li>• BIM Management Meeting Minutes</li> <li>• BIM Coordination Meeting Minutes</li> </ul>
<b>Master File</b>	Prime Consultant	Native (e.g. .rvt) and .ifc (4.X+)	Provided by the Lead BIM Manager
<b>Design Models</b>	Consultants	Native (e.g. .rvt) and .ifc (4.X+)	Submit with associated 2D deliverables at each milestone. See the BIM Requirements Appendix : Information requirements to ensure that models contain all the required information.  DWG format accepted for civil plans
<b>Issue publication and follow-up</b>	Consultants	Issues on the CDE	By the Consultant during 3D coordination periods during the design phase.
<b>2D Deliverables</b>	Consultants	.pdf	2D deliverables extracted directly from design Models.  CAD (dwg) drawings, mainly for architecture, can be requested at 100% preliminary and final stages, by exporting from Revit using the default Revit graphics standards.

## Notes:

- All 3D deliverables should be exported to an IFC format version 4.x+.
- IFC classes should match each component usage.
- Walls and Structural elements should be split by level.

## 8. BIM MANAGEMENT PROCESS

### 8.1 COLLABORATION PROCESS

#### 8.1.1 COMMON DATA ENVIRONMENT (CDE)

##### 8.1.1.1 OBJECTIVES

[Developer Name] mandates the deployment of a project-specific Common Data Environment (CDE) to meet the following objectives:

- Facilitate information exchange and access between stakeholders
- Facilitate project coordination
- Avoid duplication, decentralization of project information and parallel directories
- Standardize project document management

[Developer Name] will provide a document management platform to support deliverables submittals. In addition to this platform, the proposed solution(s) will be selected by the Prime Consultant, to be approved by [Developer Name] following these guidelines:

- The necessary licenses must be provided for each stakeholders requesting access.
- All procedures specific to the use of these platforms by stakeholders external to [Developer Name] must be presented in the BIM Execution Plan (BEP).
- The folder tree must follow standards established by [Developer Name].

##### 8.1.1.2 SUBMISSION MANAGEMENT

Models, plans and specifications (Submissions) must be uploaded on the CDE in accordance with the principles set out below:

#### States of files uploaded to the platform:

- "SHARED": This state refers to regular Submissions of Models on the CDE for interdisciplinary collaboration purposes.
- "PUBLISHED": This state refers to the submission of deliverables for official handover of Models on the CDE for evaluation, use and archiving by [Developer Name].

Note: For each Submission on the document management platform, a Submission is also expected on the additional solutions selected by the Prime Consultant.

##### 8.1.1.2.1 SHARED STATE

Models must be filed in the "SHARED" folder of the relevant discipline.

#### Sharing Frequency:

- By each Consultant,
  - In the design phase, preliminary plans and specifications, on a weekly **basis\***.

- During the construction phase, on a weekly **basis**\* until the last lot has been issued by all the stakeholders involved (Consultant and Contractors-Lot) and on an ad hoc basis for each Change Directive or Change Order or other modifications issued that have an impact on the modeling after the last lot has been issued.

\* The day of the week scheduled for these Submissions must be specified in the BIM Execution Plan (BEP). In the specific case where no changes have been made since the previous version was submitted, the new submission may be delayed. At any time during the project, a model exchange cycle may not exceed 30 calendar days.

**Revision management:**

These SHARED Submissions must be made using the revision management functions of the platforms in place, without modifying the file names, in order to facilitate access to the Models and tracking of the Submissions.

**8.1.1.2.2 PUBLISHED STATE**

Deliverables must be submitted in the sub-folder dedicated to the project milestone (e.g. "Schematic Design"), included in the "DELIVERABLES" folder for the discipline concerned.

**Frequency of Submissions:**

Models, plans and specifications for "DELIVERABLES" must be submitted in a unique manner according to the key milestones identified for the project.

**8.1.1.3 ACCESS MANAGEMENT AND GOVERNANCE**

Except for the document management platform, solution(s) access rights are managed by the Prime Consultant. Any request for access to the platforms making up the CDE must be made by e-mail to the person in charge indicated by the parties involved in the BIM Execution Plan (BEP).

---

**8.1.2 BIM MEETINGS**

All BIM meetings must be conducted using the Reference Models for the current phase as a support.

**8.1.2.1 KICK-OFF**

Objective: define common collaboration principles, the technological ecosystem, the BIM Requirements guidelines and to clarify the teams' vision at the start of the design phase. At this meeting, [Developer Name] will outline its vision, objectives and requirements for the BIM approach to the project.

Table 5 - BIM Design Kick-off Meeting

Manager	Lead BIM Manager
Participants	<ul style="list-style-type: none"> <li>Representatives of [Developer Name]</li> <li>BIM managers</li> <li>Design project managers</li> </ul>
Frequency	Unique

#### 8.1.2.2 BIM MANAGEMENT

Objective: provide a framework for the BIM process, and to communicate and address any problems encountered during the execution of the processes defined in the BIM Execution Plan and the BIM requirements.

Table 6 - BIM management meeting

Manager	Lead BIM Manager
Participants	<ul style="list-style-type: none"> <li>Representatives of [Developer Name]</li> <li>BIM Managers</li> <li>Design project managers as needed</li> </ul>
Frequency	As needed every 4 weeks

#### 8.1.2.3 VALIDATION OF DESIGN COORDINATION

Objective: support interdisciplinary coordination during the design phase. The Lead BIM Manager presents current construction issues, so that the consultants can identify possible solutions and assign resolution responsibilities. The Prime Consultant retains responsibility for coordinating the work with the number of coordination workshops they deem appropriate.

Note: Coordination activity is based on Design Models and is recorded in the collaborative platform.

Table 7 - Design Coordination Meetings

Manager	Lead BIM Manager
Participants	<ul style="list-style-type: none"> <li>Representatives of [Developer Name]</li> <li>BIM discipline managers</li> <li>Design project managers</li> </ul>
Frequency	At the coordination milestone during the preliminary plans and specifications design phase

## 8.2 DESIGN CHANGE MANAGEMENT

The purpose of DASH with BIM integration is to eliminate the need for Change Orders. However, should Change Orders be necessary, during the construction phase, each Change Order issued must be represented and managed using the Design Models. The Design team must publish a revised version of their discipline model with each Change Order.

## 9. QUALITY ASSURANCE AND CONTROL

### 9.1 QUALITY ASSURANCE PLAN

The Lead BIM Manager is responsible for establishing a quality assurance plan to be detailed in the BIM Execution Plan (BEP) in collaboration with the discipline BIM Managers, who must themselves adhere to it and ensure that it is implemented and followed within their respective teams. The respective BIM Managers of each discipline must also establish a quality assurance procedure to validate that the processes for creating and updating information in their discipline adequately meet the requirements and standards defined by [Developer Name]. Each project member is responsible for carrying out quality assurance for the dataset and models before submitting their deliverables.

This quality assurance plan must include, but is not limited to, the following points:

- Modeling guidelines: Ensure that each model is created based on the modeling requirements and standards of [Developer Name].
- Information validation: Ensure that the geometric and alphanumeric information required by [Developer Name] during the various project milestone deliveries complies with BIM Requirements and is properly presented.
- Status of communications and collaboration: Ensure prompt resolution of issues and conflicts in the collaborative platform (communications must be validated by the Lead BIM Manager on an ongoing basis on the project). In addition, collaboration processes (repository management, frequency of Model exchange, timely information updates, etc.) must be periodically audited to ensure efficiency and prevent potential problems. Changes between two versions of the same file must be communicated to the project team.
- Quality control: The Lead BIM Manager must carry out audits of the models, including their state of health, on an ongoing basis and just before the deliverables are handed over.
- Interference checking: In addition to continuous visual detection of coordination problems based on Models, automated detection of collisions between various Design Models must be planned by the Lead BIM Manager in collaboration with their respective Project Managers and carried out as the project progresses. To ensure the relevance and effectiveness of these checks, the Models used must have been validated in advance by the Consultants' BIM Managers.
- Project and model shall be designed with a prefabrication first design approach, ensuring the building can be produced with off-site methods without requiring extensive design changes.

Note: The list of quality control points defined in the Appendix - Information requirements can serve as a reference and starting point for stakeholders to identify potential quality issues and set up their quality assurance plan.